

# ARGENTA SERIES

## IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 600x400x200 OPAQUE DOOR

Reference:  
**GN604020**

### Characteristics:

|                                  |  |
|----------------------------------|--|
| <b>Product type:</b>             | Wall-mounting cabinet  |
| <b>Dimensions cabinet:</b>       | (AxBxC) 600x400x200 mm   |
| <b>Installation:</b>             | Surface  |
| <b>Type of door:</b>             | Single opaque door   |
| <b>Locking:</b>                  | 5-mm double-bit lock - Two 1-point lock  |
| <b>Finish:</b>                   | Coated with primer, and hardened polyester paint, embossed, with UV protection   |
| <b>Colour:</b>                   | Grey RAL 7035  |
| <b>Mounting plate:</b>           | With flat mounting plate. 2-mm galvanised sheet steel  |
| <b>Weight (Kg):</b>              | 14,0565  |
| <b>Materials:</b>                | Cold-rolled steel EN 10130+A1<br>Sheet thickness. Body: 1,2 mm. Door: 1,2 mm. Cable entry lid: 2 mm.<br>Injected polyurethane sealing gasket |
| <b>Capacity:</b>                 |  |
| <b>Maximum acceptable loads:</b> | Total load: 225 Kg. Door: 25 Kg. Plate: 200 Kg.  |

### Technical data:

|                                   |                       |
|-----------------------------------|-----------------------|
| <b>Degree of protection:</b>      | IP66 / NEMA 1, 12, 4  |
| <b>Resistance to impact:</b>      | IK10                  |
| <b>Ambient temperature range:</b> | -25 °C / +40 °C       |
| <b>Maximum operating voltage:</b> | 1000 V AC / 1500 V DC |

### Certificates and standards:

|                      |   |
|----------------------|---|
| <b>Directive:</b>    | 2014/35/EU  |
| <b>Standards:</b>    | UNE-EN 62208 and UNE-EN 61439-1-3 (as applicable) |
| <b>Certificates:</b> | UL508A / Bureau Veritas                           |



### Codes:

|                               |               |
|-------------------------------|---------------|
| <b>EAN:</b>                   | 8431044490632 |
| <b>Customs tariff number:</b> | 85.38.10.00   |
| <b>ETIM 8.0:</b>              | EC000261      |

# ARGENTA SERIES

## IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 600x400x200 OPAQUE DOOR

Reference: GN604020



Standard drawing



**Detailed drawing:** <http://www.ide.es/downloads/planos/pdf/GN604020.pdf>  
<http://www.ide.es/downloads/planos/dxf/GN604020.dxf>  
<http://www.ide.es/downloads/planos/stp/GN604020.stp>

|                                 |                                     |   |                           |
|---------------------------------|-------------------------------------|---|---------------------------|
| <b>Dimensions cabinet:</b>      | (AxBxC) 600x400x200 mm              | <b>Cable entry:</b>                       | (DxE) 125x285 mm          |
| <b>Body to be flush-fitted:</b> | -                                   | <b>Wall fixing:</b>                       | (HeightxWidth) 560x360 mm |
| <b>Inside usable space:</b>     | (HeightxWidthxDepth) 550x350x179 mm | <b>Glass dorr with transparent panel:</b> | -                         |

### Sustainability:

RoHS - REACH

### Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied unassembled inside the packaging.

### Product end of life:

It does not require specific recycling operations.

### Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.