

ARGENTA SERIES

IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 600x500x250 OPAQUE DOOR

Reference:
GN605025

Characteristics:

| | |
|----------------------------------|--|
| Product type: | Wall-mounting cabinet |
| Dimensions cabinet: | (AxBxC) 600x500x250 mm |
| Installation: | Surface |
| Type of door: | Single opaque door |
| Locking: | 5-mm double-bit lock - Two 1-point lock |
| Finish: | Coated with primer, and hardened polyester paint, embossed, with UV protection |
| Colour: | Grey RAL 7035 |
| Mounting plate: | With flat mounting plate. 2-mm galvanised sheet steel |
| Weight (Kg): | 18,7451 |
| Materials: | Cold-rolled steel EN 10130+A1 Sheet thickness. Body: 1,2 mm. Door: 1,5 mm. Cable entry lid: 2 mm. Injected polyurethane sealing gasket |
| Capacity: | |
| Maximum acceptable loads: | Total load: 275 Kg. Door: 25 Kg. Plate: 250 Kg. |

Technical data:

| | |
|-----------------------------------|-----------------------|
| Degree of protection: | IP66 / NEMA 1, 12, 4 |
| Resistance to impact: | IK10 |
| Ambient temperature range: | -25 °C / +40 °C |
| Maximum operating voltage: | 1000 V AC / 1500 V DC |

Certificates and standards:

| | |
|----------------------|---|
| Directive: | 2014/35/EU |
| Standards: | UNE-EN 62208 and UNE-EN 61439-1-3 (as applicable) |
| Certificates: | UL508A / Bureau Veritas |



Codes:

| | |
|-------------------------------|---------------|
| EAN: | 8431044490694 |
| Customs tariff number: | 85.38.10.00 |
| ETIM 8.0: | EC000261 |

ARGENTA SERIES

IP66 STEEL WALL-MOUNTING CABINETS

Description: IP66 ROLLED STEEL WALL-MOUNTING CABINET 600x500x250 OPAQUE DOOR

Reference: GN605025



Standard drawing

Detailed drawing: <http://www.ide.es/downloads/planos/pdf/GN605025.pdf>

<http://www.ide.es/downloads/planos/dxf/GN605025.dxf>

<http://www.ide.es/downloads/planos/stp/GN605025.stp>



| | | | |
|---------------------------------|-------------------------------------|---|---------------------------|
| Dimensions cabinet: | (AxBxC) 600x500x250 mm | Cable entry: | (DxE) 125x385 mm |
| Body to be flush-fitted: | - | Wall fixing: | (HeightxWidth) 560x460 mm |
| Inside usable space: | (HeightxWidthxDepth) 550x450x229 mm | Glass dorr with transparent panel: | - |

Sustainability:

RoHS - REACH

Supply:

Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied unassembled inside the packaging.

Product end of life:

It does not require specific recycling operations.

Recommended applications:

Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.