

Gaminio duomenų lentelė

Specifikacijos



Fire detection panel, Esmi Sense FDP252, LT

FFS00703920LT

Main

Range of product	Esmi fire detection panels
Product or component type	Control panel
Number of batteries	2 x 12 V 17 Ah
Colour	Cover light grey NCS S 1005-R80B) Frame dark grey NCS S 7502-B)
Maximum allowed current consumption	1.0 A 24 V DC standby 4.8 A 24 V DC alarm

Complementary

Mains supply power	165 VA
Mains supply voltage	230 V AC +/- 10 % 50...60 Hz
Operating voltage range	19...30 V DC
Device composition	cover plastic frame sheet steel/plastic back frame sheet steel
Height	580,0 mm
Width	430,0 mm
Depth	142,0 mm
Product weight	10,6 kg without batteries
Addressable loop controller	ALC2/SLC
Number of loops	8 addressable
Number of addresses	0...159 addressable detectors and call points for SLC 0...159 other modules for SLC 0...126 addressable devices for ALC
Optional circuit board slots	5 optional circuit board
Product compatibility	Fireman's panel FMP Protocol repeater REP/REPX-OB Delay alarm panel DAP Logical controller MCO/MCOX-OB LED panels for fire zones ZLPX

Environment

Standards	EN 54-2 EN 54-4
Relative humidity	0...94 % non-condensing

Ambient air temperature for operation	5...40 °C
Ambient air temperature for storage	0...50 °C
IP degree of protection	IP30

Offer Sustainability

Tvaraus pasiūlymo statusas	„Green Premium“ gaminys
REACH direktyva	REACH deklaracija
ES RoHS direktyva	Atitinka ES RoHS deklaracija
Be gyvsidabrio	Taip
RoHS išimčių informacija	Taip
Kinijos RoHS direktyva	Kinijos RoHS deklaracija Produktas neįeina į Kinijos RoHS apimtį. Medžiagų deklaracija pateikiama jūsų informacijai.
Aplinkosauginės informacijos atskleidimas	Produkto aplinkosaugos profilis
Žiedinės ekonomikos profilis	Eksploatavimo ciklo pabaigos informacija
WEEE	Šį produktą Europos Sąjungos rinkose reikia utilizuoti perduodant į specialias surinkimo vietas ir negalima išmesti su buitinėmis atliekomis.

Contractual warranty

Garantija	24 months
-----------	-----------