

ENSTO

Atšakinis gnybtas

SL11.11



Tipas	SL11.11
GTIN	6418677403507
Pavadinimas	Atšakinis gnybtas Al 10-95 mm ² arba Cu 1,5-70 mm ²
Aprašymas	Universalus gnybtas tinka visiems aliuminio ir vario, pagrindinio ir atšakos laidininku sujungimams. Pagrindinis laidininkas Al 10-95mm ² arba Cu 1,5-70mm ² . Atšakos laidininkas Al 10-95mm ² arba Cu 1,5-70mm ² .
Gamintojas	Ensto Finland Oy

Techninė specifikacija

Sertifikatai

Standartinis žymėjimas:	VDE 220 Teil 1/11.71 and Teil 2/11.71,SFS 2663
-------------------------	------------------------------------------------

Matmenys

Ilgis:	76 mm
Pagrindinis laidininkas mm ² :	Al 10-95 / Cu 1.5-70
Atšakos laidininkas mm ² :	Al 10-95 / Cu 1.5-70
Plotis:	60 mm
Aukštis:	46 mm
Laidininko skersmuo:	3 ... 16 mm
Neto svoris:	0,1147 kg

Savybės

Varžtas:	M8
----------	----

Mechaninės savybės

Užveržimo momentas:	20 Nm
---------------------	-------

Kita

ETIM Class:	EC001062
-------------	----------

ETIM Techninė specifikacija

etim

Nominal cross section main conductor SM:	1,5 ... 95 mm ²
Nominal cross section branch conductor SE/RE:	1,5 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	1,5 ... 95 mm ²
Material main conductor:	Aluminium/copper
Material branch conductor:	Aluminium/copper
Terminal insulated:	Yes
Clamping channel opening main conductor:	Closed
Clamping channel opening branch conductor:	Closed
Surface protection:	Tinned
Type of connection:	Insulation piercing connector IPC

Pakuotė

Paletė

Package size:	3150 pce
Depth:	1200 mm
Width:	800 mm
Height:	1050 mm

Pakuotė

Package size:	50 pce
Depth:	385 mm
Width:	260 mm
Height:	130 mm
Weight:	6,235 kg
Volume:	13,013 l