

# ENSTO

## Varžtinis antgalis

SML2.27

Tipas	SML2.27
GTIN	6418677457562
Pavadinimas	Varžtinis antgalis Al/Cu 70-240mm <sup>2</sup> , Ø13
Aprašymas	Antgalis skirtas vidutinės įtampos iki 36 kV kabeliu laidininkams prijungti. Antgalis tinka aliuminio ir vario laidininkams, yra sandarus vandeniui bei tinkamas ištiesinems ar daugiavielemis, sektorinėms ar apvalioms laidininkų gysloms.
Gamintojas	Ensto Finland Oy



## Techninė specifikacija

### Sertifikatai

Standartinis žymėjimas: IEC 61238-1

### Matmenys

Nominal cross section: 70 ... 240 mm<sup>2</sup>

Laidininko skerspjūvis Al: 70 ... 240 mm<sup>2</sup>

Laidininko skerspjūvis Cu: 70 ... 240 mm<sup>2</sup>

Neto svoris: 0,2 kg

### Savybės

For conductor shape: Solid, Sector, Stranded, Round

For busbar type: Bare copper busbar, Bare aluminium busbar, Tinned busbar

### Mechaninės savybės

Užveržimo momentas: 35 Nm

### Kita

ETIM Class: EC001054

## ETIM Techninė specifikacija

---

### etim

Nominal cross section copper RM:	70 ... 240 mm <sup>2</sup>
Nominal cross section copper RE:	70 ... 240 mm <sup>2</sup>
Nominal cross section copper SM:	70 ... 240 mm <sup>2</sup>
Nominal cross section aluminium SM:	70 ... 240 mm <sup>2</sup>
Nominal cross section aluminium SE:	70 ... 240 mm <sup>2</sup>
Bolt dimension (metric):	24
Material conductor:	Aluminium/copper
Surface protection:	Tinned
With shear-off head:	Yes

### Pakuotė

---

#### Paletė

Package size:	1050 pcs
Depth:	1200 mm
Width:	800 mm
Height:	890 mm

#### Pakuotė

Package size:	10 pcs
Depth:	220 mm
Width:	220 mm
Height:	125 mm
Weight:	2,55 kg
Volume:	6,05 l