



Ledinaire Waterproof Tube Housing

WT050C 2xTLED L1200

- 220 to 240 V - 50 or 60 Hz - Safety class II - - - IP65 | Dust penetration-protected, jet-proof - IK08 | 5 J vandal-protected - White

The Ledinaire waterproof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.

Product data

General Information		Input Frequency	
Luminaire light beam spread	-	Input Frequency	50 or 60 Hz
Protection class IEC	Safety class II	Mechanical and Housing	
Material	Polycarbonate	Overall length	1,275 mm
Angle	-	Overall width	95 mm
Accessory color	White	Overall height	84 mm
Brand	Philips	Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm
Value ladder	Value	Approval and Application	
Light Technical		Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Color rendering index (CRI)	-	Mech. impact protection code	IK08 [5 J vandal-protected]
Operating and Electrical		Product Data	
Input Voltage	220 to 240 V	Full product code	871016336603699
Line Frequency	50 or 60 Hz	Order product name	WT050C 2xTLED L1200

Ledinaire Waterproof Tube Housing

Order code	911401807481
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	9
Material number (12NC)	911401807481
Net weight	0.950 kg

Full product name	WT050C 2xTLED L1200
EAN/UPC - Case	8710163366197



Dimensional drawing

